

5 OUTBOARD
YEARS
warranty

FOR LEISURE USE ONLY
Subject to terms and conditions
see your Dealer for more
information.

**Stile
Line**

**Evolution
Line**

**Professional
Line**



f Selva Marine



**INFLATABLE BOATS
WITH OUTBOARD
MOTOR**

MODEL
700 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 699 | 276 | 1000 | 14 |

MODEL
650 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 650 | 260 | 580 | 12 |

MODEL
600 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 599 | 263 | 480 | 10 |

MODEL
570 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 570 | 255 | 400 | 9 |

MODEL

540 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 535 | 243 | 340 | 8 |

MODEL
500 STILE



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 495 | 230 | 305 | 8 |

TECHNICAL CHARACTERISTICS

| Model | 700 STILE | 650 STILE | 600 STILE | 570 STILE | 540 STILE | 500 STILE |
|---|------------------------------------|-------------------------------|-----------|-----------|-----------|-----------|
| Max length (cm) | 699 | 650 | 599 | 570 | 535 | 495 |
| Internal length (cm) | 624 | 605 | 550 | 480 | 459 | 417 |
| Max width (cm) | 280 | 260 | 263 | 255 | 243 | 230 |
| Internal width (cm) | 153 | 145 | 143 | 131 | 121 | 121 |
| Construction height (cm) | 93 | 92 | 92 | 80 | 80 | 80 |
| Tube diameter (cm) | 50÷58 | 50÷60 | 50÷60 | 50÷62 | 50÷62 | 51÷57 |
| Motor shaft version | 1 XL | 1 XL | 1 L | 1 L | 1 L | 1 L |
| Number of compartments | 6 | 5 | 5 | 5 | 5 | 5 |
| Number of lockers | 6 | 6 | 6 | 5 | 5 | 4 |
| Dry weight ex motor, fittings, liquids (kg) | 1080 | 580 | 480 | 400 | 340 | 305 |
| People carrying capacity | 14 | 12 | 10 | 9 | 8 | 8 |
| Max carrying load (kg) <i>(people, standard equipment, engine)</i> | 1380 | 1480 | 1150 | 1060 | 900 | 900 |
| Inflation pressure (atm) | 0,2 | 0,2 | 0,2 | 0,2 | 0,2 | 0,2 |
| Max applicable power (kW/hp) | 221 (300) | 129 (175) | 126 (171) | 100 (136) | 85 (115) | 66 (90) |
| Recommended power (min/max hp) | 200 / 225 | 115 / 150 | 80 / 115 | 70 / 115 | 60 / 100 | 50 / 80 |
| Hull type | DEEP-V WITH REST SKIDS | | | | | |
| Hull material | GRP - DOUBLE MOULDED | | | | | |
| Internal hull colour | White | | | | | |
| External hull colour | White | | | | | |
| Fabric | NEOPRENE - HYPALON 1500 g/mq | NEOPRENE - HYPALON, 1300 g/mq | | | | |
| Design category | B | C | C | C | C | C |

For information on engines in packages with **STILE LINE** boats please see the Selva Marine outboard engine catalogue.
The data in this table are to be considered as approximate and **Selva S.p.A.** reserves the right to modify the technical characteristics, materials, construction, weights, colours, graphics etc. without any forewarning or obligation. The specifications given in this table are determined in accordance with regulations in force at the time of preparation of the catalogue and may have to be modified. Please request confirmation of the data at time of purchase.

EQUIPMENT

| Equipment | 700 STILE | 650 STILE | 600 STILE | 570 STILE | 540 STILE | 500 STILE |
|--|-------------|-------------|-------------|-------------|-------------|-----------|
| Handrails on fabric tubulars | S | S | S | S | S | S |
| Handrail in fabric on tubes | S | S | S | S | S | S |
| Pair of paddles | S | S | S | S | S | S |
| Inflating pump | S | S | S | S | S | S |
| Motor installation | S | S | S | S | S | S |
| Complete 'STILE LINE' console ⁽¹⁾ | S | S | S | S | S | S |
| Steering wheel "SELVA SPORT" | S | S | S | S | S | S |
| Driver's seat ⁽²⁾ | N | N | N | N | N | S |
| Multifunctional driver's seat ⁽³⁾ | S | S | S | S | S | N |
| Engine instruments | S | S | S | S | S | S |
| Instrument panel full extension | S | S | S | S | S | S |
| Switch panel with switches | S | S | S | S | S | S |
| Stern sofa convertible into sundeck | S | S | S | S | S | N |
| Bow sundeck cushions | S | S | S | S | S | S |
| Bow sundeck extension | N | S | S | S | S | S |
| Cushion for bow sundeck extension | N | S | S | S | S | S |
| Stern sundeck extension with cushion | S | S | N | N | N | N |
| STILE LINE cushions two-tone : Colorado/Gange | S | S | S | S | S | S |
| Foldable stainless steel ladder | O | O | O | O | O | O |
| Stern platforms in GRP with stainless steel ladder | O | O | O | O | O | N |
| Auxiliary motor support | O | O | O | O | O | O |
| Sun awning | O | O | O | O | O | O |
| "Twin-tube" stainless steel, telescopic, tilt-up rollbar with start lights and horn | O | O | O | O | O | O |
| Mooring cover | O | O | O | O | O | O |
| Built-in fuel tank installed with blower, delivery pipe with water/fuel separating filters and solenoid valves, filling pipe, breather pipe and fuel level gauge | S - 200 lt. | S - 175 lt. | S - 140 lt. | O - 140 lt. | O - 140 lt. | N |
| Complete shower system with integrated fresh water tank | S - 50 lt. | S - 40 lt. | S - 40 lt. | O - 40 lt. | N | N |
| GRP bow pulpit with electric winch, stainless steel anchor and chain | S | O | N | N | N | N |
| Immersion bilge pump | S | S | S | S | S | S |
| Hydraulic steering system | S | S | O | O | O | N |

(1) Console complete with: stainless steel handrails, single lever remote control box, anatomic steering wheel, single-cable steering system, (hydraulic steering system for models 650 STILE e 700 STILE, antireflection windscreen, door with lock, front seat with cushion and access to locker underneath plus backrest cushion.

(2) For model 500 STILE cushion seat with hinges and lock for access to stern locker.

(3) For the 540 STILE to 700 STILE models = half upright driver's seat with cushion and access to lower locker.

Selva S.p.A. reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

S = Standard O = Optional N = Not available

MODEL

D.650 FAMILY SPECIAL



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 650 | 260 | 580 | 12 |

D.650 FAMILY SPECIAL



FAMILY AREA AT STERN

The aft deck easily converts into a comfortable 'U'-shape sofa to create practical room as a large sunbed or where a large table can be fitted for leisurely meals.

MODEL

D.570 FB



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 570 | 255 | 400 | 9 |



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 535 | 243 | 340 | 8 |

TECHNICAL CHARACTERISTICS

| Model | D.650 FAMILY | D.570FB | D.540 |
|---|--------------------------------|-----------|----------|
| Max length (cm) | 650 | 570 | 535 |
| Internal length (cm) | 605 | 480 | 459 |
| Max width (cm) | 260 | 255 | 243 |
| Internal width (cm) | 145 | 131 | 121 |
| Construction height (cm) | 92 | 80 | 80 |
| Tube diameter (cm) | 50÷60 | 50÷62 | 50÷62 |
| Motor shaft version | 1 XL | 1 L | 1 L |
| Number of compartments | 5 | 5 | 5 |
| Number of lockers | 6 | 5 | 5 |
| Dry weight ex motor, fittings, liquids (kg) | 580 | 400 | 340 |
| People carrying capacity | 12 | 9 | 8 |
| Max carrying load (kg) <i>(people, standard equipment, engine)</i> | 1480 | 1060 | 900 |
| Inflation pressure (atm) | 0,2 | 0,2 | 0,2 |
| Max applicable power (kW/hp) | 129 (175) | 100 (136) | 85 (115) |
| Recommended power (min/max hp) | 115 / 150 | 70 / 115 | 60 / 100 |
| Hull type | DEEP-V WITH REST SKIDS | | |
| Hull material | GRP - DOUBLE MOULDED | | |
| Internal hull colour | WHITE | | |
| External hull colour | WHITE | | |
| Fabric | NEOPRENE - HYPALON, 1300 g/sqm | | |
| Design category | C | C | C |

For information on engines in packages with **EVOLUTION LINE** boats please see the **Selva Marine** outboard engine catalogue. The data in this table are to be considered as approximate and **Selva S.p.A.** reserves the right to modify the technical characteristics, materials, construction, weights, colours, graphics etc. without any forewarning or obligation. The specifications given in this table are determined in accordance with regulations in force at the time of preparation of the catalogue and may have to be modified. Please request confirmation of the data at time of purchase.

| Equipment | D.650 FAMILY | D.570FB | D.540 |
|--|-------------------|------------|------------|
| | Evolution Special | Evolution | Evolution |
| TWIN COLOUR TUBE - WHITE/BLACK CARBON | S | N | N |
| Handrail in fabric on tubes | S | N | N |
| Pair of paddles | S | S | S |
| Inflating pump | S | S | S |
| Motor installation | S | S | S |
| Complete electrical system | S | S | S |
| Complete console ⁽¹⁾ | S | S | S |
| Volante Special | S | N | N |
| Multi-purpose driving seat ⁽²⁾ | S | S | S |
| Engine instrumentation | S | S | S |
| Instrument panel with carbon look | S | N | N |
| Stern sofa converts for sunbathing or to stretched legs seat | S | S | S |
| Bow sundeck cushions | S | S | S |
| Bow sundeck extension | S | S | S |
| Cushion for bow sundeck extension | S | S | S |
| Stern sundeck extension with cushion | S | N | N |
| Cushions in "special" double colour | S | N | N |
| Foldable stainless steel ladder | O | O | O |
| Stern platforms in GRP with stainless steel ladder | S | O | O |
| Auxiliary motor support | O | O | O |
| Sun awning | O | O | O |
| *Twin-tube* stainless steel, telescopic, tilt-up rollbar with start lights and horn | O | O | O |
| Mooring cover | O | O | O |
| Built-in fuel tank installed with blower, delivery pipe with water/fuel separating filters and solenoid valves, filling pipe, breather pipe and fuel level gauge | S - 175 lt. | O - 86 lt. | O - 86 lt. |
| Built in fibreglass fresh water tank with fitting for shower | S - 40 lt. | O - 40 lt. | N |
| GRP bow pulpit with electric winch, stainless steel anchor and chain | O | N | N |
| Immersion bilge pump | S | S | S |
| Hydraulic steering system | S | O | O |

(1) Console complete with: stainless steel handrails, single lever remote control box, anatomic steering wheel, single-cable steering system, (hydraulic steering system for models D.650 Family) antireflection windscreen, door with lock, front seat with cushion and access to locker underneath plus backrest cushion.

(2) Semi-upright driver's seat with cushion and access to lower locker

Selva S.p.A. reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

S = Standard O = Optional N = Not available
O/N = Optional for versions with single engine, Not available for versions with double engine

MODEL
600 PRO



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 599 | 259 | 460 | 14 |



| Max length (cm) | Max beam (cm) | Dry weight (kg) | People carrying capacity |
|-----------------|---------------|-----------------|--------------------------|
| 545 | 246 | 320 | 10 |

TECHNICAL CHARACTERISTICS

| Model | 600 PRO | 550 PRO |
|---|-------------------------------|----------|
| Max length (cm) | 599 | 545 |
| Internal length (cm) | 550 | 468 |
| Max width (cm) | 259 | 246 |
| Internal width (cm) | 143 | 121 |
| Construction height (cm) | 92 | 80 |
| Tube diameter (cm) | 50÷60 | 50÷62 |
| Motor shaft version | 1 L | 1 L |
| Number of compartments | 5 | 5 |
| Number of lockers | 4 / 5 | 3 / 4 |
| Dry weight ex motor, fittings, liquids (kg) | 460 | 320 |
| People carrying capacity | 14 | 10 |
| Max carrying load (kg) | 1510 | 1100 |
| Inflation pressure (atm) | 0,2 | 0,2 |
| Max applicable power (kW/hp) <i>(people, standard equipment, engine)</i> | 126 (171) | 85 (115) |
| Recommended power (min/max hp) | 80 / 115 | 60 / 100 |
| Hull type | DEEP V WITH REST SKIDS | |
| Hull material | GRP DOUBLE MOULDED | |
| Internal hull colour | GREY | |
| External hull colour | GREY | |
| Fabric | NEOPRENE - HYPALON, 1300 g/mq | |
| EC standard design category | C | C |

For information on engines in packages with **PROFESSIONAL LINE** boats, see outboard engine catalogue.

The data in this table are to be considered as approximate and **Selva S.p.A.** reserves the right to modify the technical characteristics, materials, construction, weights, colours, graphics etc. without any forewarning or obligation.

The specifications given in this table are determined in accordance with the regulations in force at the time of preparation of the catalogue and may have to be modified. Please request confirmation of the data at time of purchase.

EQUIPMENT

| Equipment | 600 PRO | 550 PRO |
|--|-------------|------------|
| Pair of paddles | S | S |
| Inflating pump | S | S |
| Motor installation | S | S |
| Complete electrical system | S | S |
| Complete console (1) (2) | S | S |
| Roller backrest seat for semi-erect driving with stainless steel support (2) | S/N | S/N |
| Central semi-erect seat in fibreglass with access to internal locker (2) | S/N | S/N |
| Front seat console with cushion and access to locker below | S | S/O |
| Rubber fabric anthracite coloured reinforcements on tubes | S | S |
| Rope handrails for double grip also in case of lifting on board | S | S |
| PVC protection on the bow | S | S |
| Engine instrumentation | S | S |
| Switch panel | O | O |
| Foldable stainless steel ladder | O | O |
| Auxiliary motor support | O | O |
| Sun awning | O | O |
| Mooring cover | O | O |
| Built-in fuel tank installed in compliance with CE regulations with blower, delivery pipe with water/fuel separating filters and solenoid valves, filling pipe, breather pipe and fuel level gauge | S - 135 lt. | O - 86 lt. |
| Immersion bilge pump | S | S |
| Hydraulic steering system | O | O |

(1) Console complete with stainless-steel handrail, single-lever remote control box, ergonomic steering wheel, single-cable steering, anti-reflection windscreen, door with lock, front seat with cushion and access to locker below plus backrest cushion (excluded 550 PRO with central console).

(2) The 600 PRO and 550 PRO models are available in two versions, to be specified when ordering the boat, with central console and backrest seat in fibreglass or rear console and steel roller backrest seat.

Selva S.p.A. reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

S = Standard O = Optional N = Not available S/N = Standard / not available depending on ordered boat type
S/O = Standard / optional depending on ordered boat type



SELVA S.p.A.

Head office and main factory:

Viale dell'Industria, 13

23037 Tirano (SO) - Italia

Tel. 0342 702451 - Fax 0342 70536

VAT Number IT 00050830140

Company Registration SO n. 00050830140

REA n. 18382

www.selvamarine.com



Q8  **Oils**